

SPECIFICATION

Be It Known that We, **PETER C. BRUSSO**, a citizen of the United States of America , resident of Anaheim Hills, State of California and **HENRI J.A. CHARMASSON**, a citizen of the United States of America, resident of San Diego, State of California have invented
5 a new and useful

VENDING MACHINE WITH ELECTRONIC PAYMENT MEDIA

of which the following is a specification.

Prior Application

This is a continuation of Provisional Application No. 60/448,201 filed February 18, 2003.

Field of the Invention

This invention relates to vending machines, and more specifically to the type of vending machines found on jobsites capable of distributing pastries, small snack items and beverages that accept electronic payments.

Background of the Invention

Vending machines have traditionally accepted coins and occasionally bank notes in payment for the goods or service they dispense. The popularity of credit cards, debit cards and more recently, cash cards, also referred to as smart cards, has conditioned the purchasing public to use of the convenient so-called plastic money. Carrying a wallet-size card is, indeed, much more convenient than carrying a pocketful of change.

Cellular phones coupled with various forms of wireless communication including so-called Bluetooth technology further expand the spectrum of cashless payment methods soon to be readily available to the general public.

The instant invention results from an attempt to apply these new payment technologies to the operation of automatic vending machines.

Summary of the Invention

The principal and secondary objects of this invention are to facilitate access and

use of automatic vending equipment by maximizing cashless transactions and taking full advantage of wireless banking methods.

These and other valuable objects are achieved by the use of creditable and debitable smart cards which can be loaded through a bank note acceptor installed on a vending machine, then used to make small purchases on the same machine. A transaction clearing house is provided to manage the accounts of a number of automatic vending operators. The invention provide to customers, a universal cash card usable on equipment run by a wide spectrum of automated goods and service providers. Payments are made through debit cards sold by the vending machine operators to owners of vending locations for distribution to employees and customers. Payments can also be made by currency which, once deposited into the machine, are securely accumulated within the magazines and can only be retrieved at the central location with use of a special key. The selection of desired goods and payment therefor can also be made through wireless communication with a cell-phone or other hand-held device. At certain locations, combinations of beverage and snack food item vending machines work together to deliver specially advertised combinations obtainable at a discount price. Magazines returned to the central location are emptied of any unsold goods and collected currency, cleaned, sanitized and refilled with fresh goods before being assigned to a route for distribution to new locations.

The machine is opened by means of another type of a chip-mounting smart card. Upon opening, the machine automatically down-loads" on the card, an account of all the sales that occurred since the last service call, including the amount of currency accumulated in the currency box. The card is returned along with the removed magazine to the distribution center where it is used to verify the integrity of the returned components and thus, deters pilferage by the service

personnel.

Brief Description of the Drawing

Figure 1 is a front elevational view of a snack-food vending machine;

Figure 2 is a horizontal, median cross-sectional view thereof;

Figure 3 is a cross-sectional view taken along line 3-3 of Figure 1;

Figure 4 is an exploded perspective view of the magazine;

Figure 5 is a cross-sectional view of the beverage vending machine;

Figure 6 is a perspective view of a beverage can magazine;

Figure 7 is a side view of the gate mechanism;

Figure 8 is a block diagram of the electronic control system;

Figure 9 is a flow diagram of the machine operation;

Figure 10 is a flow diagram of the smart card reloading process;

Figure 11 is a block diagram of a centralized account clearing system; and

Figure 12 is a flow diagram of the clearing house process..

Description of the Preferred Embodiment of the Invention

Referring now to the drawing, there is shown a compact, counter top vending machine 1 housed in a molded plastic and sheet metal cabinet 2. A substitutable, quadrangular magazine 3 is securely held into the cabinet behind the cabinet front door 4. The customer interface includes a message display 5, a keypad 6 upon which the selection of a desired goods can be made, a currency-acceptor 7, a card reader 8 and a dispensing pocket 9. The goods 10 and

the numbers of the stations or cells **11** holding them can be observed through the transparent door of the cabinet.

Each station or cell **11** can hold a plurality of goods having the same sale price. Each station is identified by a letter (A-C) and a number (1-6). In each station **11**, a plurality of goods are held between the coils of a spiral rack **13**. These goods may be of various configurations or sizes. When a spiral rack is rotated, it acts as an Archimedes screw, and shifts the goods toward the access port **14** along the front of the magazine. The magazine comprises three trays or layers **15** of good-holding station units. It should be understood that the number of stations in each unit and the number of units in a magazine can be varied to accommodate different sizes and varieties of goods. Typically, small goods such as candy bars can be loaded on a narrow cells such as the one shown on the right side of each tray. Large items such as pastries and potato chip packs that require a larger cell, can be loaded into stations such as the ones shown on the center and left side of each tray.

The lower, lateral corner of the magazine **3** rests upon shelf **16** formed inside the cabinet.

The cabinet **2** comprises an external shell **18** made of a first sheet **19** of metal bent to form the top and two opposite lateral walls, a second sheet **20** closing the back of the cabinet and a third sheet **21** forming the bottom.

A plastic liner **22** is nested within the shell **18** and through its open front. The shell and liner are joined about their respective flanged, peripheral frontal edges **23**, **24**. The liner defines a cavity **25** closed by the door **4**. The cavity is divided into a load compartment **26** which occupies its major portion, and the pocket or receptacle **9** that receives the delivered goods below

the load compartment.

The shelf **16** that separates the load compartment and the pocket is supported by an angled plate **28** secured to the three sheets **19, 20, and 21** forming the shell.

A volume of expanded, insulating polyurethane resin foam material **17** is injected
5 between the liner **22** and the shell, excluding the space **29** defined under the angled plate **28**. Once solidified, the foam material combines with the shell and liner to form a strong, yet light box. The external shell can thus be made of relatively thin sheet material whether steel, aluminum or plastic, typically, 2 mm thick. Similarly, the thickness of the plastic liner can be limited to approximately 1.5 mm.

10 The structural components of the door **4** comprise a molded top piece **30**, a molded bottom piece **31** and two extruded lateral pillars **32, 33** joining the top and bottom pieces. Those four components frame a transparent polycarbonate window panel **34**. The door is hinged along the external edge of the left pillar **33** to the joined flanged left sides of the shell and liner peripheral edges. The top and bottom pieces and the pillars are flanged along their external edges
15 so that when the door meets the joined peripheral edges of the shell and liner, the vertical center portions of the door stand apart from the front edge of the cabinet. The space therebetween defines a chute **27** through which the selected goods fall toward the pocket **9**. A resiliently compressible gasket **35** is secured to the edge of the door in order to provide a hermetic seal when the door is closed. A locking mechanism **36** with a keyhole **37** accessible at the top right edge
20 of the molded top piece **30** is used to secure the door. Overlapping flanges **38, 39** along the peripheral edges of both the cabinet and the door prevent the introduction of a prying tool between those two components. Mounted behind the top door piece **30** is a fluorescent light

fixture 40. Mounted against the back upper portion of the bottom door piece 31 is an electronic module 41 which includes the display 5, the keypad 6, the card reader 8 and the electronic control circuit for the operation of the machine. An aperture 42 in the lower portion of the bottom piece provides access to the pocket 9 into which falls the purchased goods. The aperture is secured by a swinging door 43. When the door is pushed inwardly to gain access to the goods in the pocket, it prevents access to the chute 27 and any of the goods held in the cells of the magazine.

The currency acceptor 7 is mounted against the right wall of the liner 22. The currency acceptor can accept bank notes in a number of denominations, validate them and provide a recordable coded information of the currency amount that has been accepted. An inclined channel 44 direct the accepted bank note 45 to a currency receptor box 46 in the base 47 of the magazine.

As more specifically illustrated in Figures 3 and 4, the magazine comprises the base 47 three goods-holding trays 15, a cover 48 and a pair of locking straps 49 holding all those components together. The currency receptor box 46 which occupies the right portion of the base is closed by a lid 50 secured by a lock 51. In each station or cell 11 of the trays, the back end of the spiral rack 13 is connected to a short shaft that passes through the back wall 52 of the tray where it is supported by a bearing. The shaft has a female coupling 53 shaped and sized to be engaged by a corresponding male coupling 54 of a driving mechanism. When the spiral rack is rotated 360° by the drive mechanism, one of the goods 10 is selectively expelled from its cell and falls into the pocket 9 below. The cover 48 has a folding handle 55 in its center for conveniently carrying the magazine. The locking straps 49 are shaped and dimensioned to intimately cinch the other components of the magazine together. Their crooked left ends 56 lock into mating recesses

57 in the top of the cover 48. At the bottom ends of the straps, a similar hook end 58 locks into a similar recess 59 in the base.

For each spiral rack, the driving mechanism consists of a motor assembly 60 including a control circuitry which allows the motor to make only one revolution every time it is energized. A gang of six motor assemblies packaged in a sealed driving module 61 is mounted in recesses 62 in the liner's back wall behind each tray 15.

The wirings of the motor assembly in each driving module are brought to a pigtail connector 63A that mates with a corresponding connector 63B on the main wiring harness 63 leading to the electronic control module 41 located in the cabinet door. The driving modules are held in place by snapping fasteners. Accordingly, driving modules with different numbers of motor assemblies can be quickly substituted for one another to match the composition of the trays.

A detachable cover 12 is attached to the front of the magazine, in order to close all the access ports 14 during transportation to and from the central service facilities.

An electronic sensor 65 in the chute 27 detects the passage of the goods toward the distributing pocket. The output of the sensor is fed to the microprocessor 66 which constitutes the principal component of the electronic module 41. The microprocessor typically includes a storage memory or equivalent recording medium. An infrared transceiver 68 provides access to the micro-processor data. This transceiver may be used by a service person to read useful information such as money paid, and goods sold using a wireless phone or any other type of hand-held downloading device well known to persons skilled in the art of data-processing, that can provide a communication interface with various types of devices and networks according to

so-called "Bluetooth" technology.

The transceiver **68** can also respond to an order for goods and payment therefor from similar wireless communication devices.

It can now be understood that once a user has made a selection by dialing on the keypad **6**, the identification of the station holding the desired type of goods and has paid as will be explained below for his purchase, the good-extracting mechanism servicing that particular station can then be activated to cause the goods most frontally located on the spiral rack to fall through the chute **27** into the dispensing pocket **9**.

As shown in Figures 8 and 9, the operation of the vending machine is controlled by the microprocessor **66**. The motors are controlled by motor-control modules **69**, and the address-decoder **70**. The motor-control modules and the address decoder consist essentially of gated current drivers, that, under control of the microprocessor, feed the forward current to the two appropriate motor. A modem **71** provides the communication interface to the microprocessor via conventional phone carrier services and/or via the Internet. An LCD message display **72** which is part of display **5** in the cabinet door is used to suggest to the user an alternate selection when the selected items is not available and to flash other notices as will be explained below. A power supply **73** is housed under the angled plate **28**. A wire harness **74** connecting the power supply to the light **40** and to the electronic module **41** is the only component that passes through the liner **22**.

As more specifically illustrated in Figure 9, the operation of the machine begins **101** when a payment card has been inserted **101** or when an alternate form of payment such as an electronic transfer through the Internet, or out of a palm-held wireless device has been

acknowledged **102** and the form of payment has been validated **103**. The system waits for the user to dial his choice of goods beginning with the letter corresponding to the proper row. The system first determines whether it is a credit card **104**. In that case, the card owner's identification is read **105**, and a credit check is initiated **106** via the modem **71**. If credit is refused, the user is
5 so advised by the display **108** of a rejection message. If the credit card owner has sufficient credit, the system waits for the user's selection. If the card is not a credit card, the system assumes that it is a debit, or so-called "smart card", and reads the card for the available balance **109**. If the balance is not sufficient to pay for one of the offered goods, a rejection message is displayed **108**. If that balance is sufficient to cover a purchase **110**, the system waits for the user's selection.

10 Once the user has selected a row **111**, that row identification is entered **112** into the microprocessor. The system then waits for the dialing of the appropriate column **113**. When the column is dialed, its identification is entered into the computer **114**. At that point, the corresponding motor is started **115** and, at the same time, a ten-second timer is also started **116**. If the timer expires **117** before the electronic sensor **65** detects the passage of goods into the
15 dispensing pocket, the motor is stopped **118** and a message suggesting an alternate selection **119** is displayed. A twenty second timer is also started **120**. If that timer runs out **121** before a new row letter is dialed by the user, the card is rejected **122**. If a row letter is dialed before the expiration of the timer **123**, the system proceeds with the entering of the row identification **112**; then the column identification **114** as previously described. If the electronic sensor **65** detects the
20 passage of the goods **124** before the ten-second timer runs out, the motor is stopped **125**. In the event of wireless payment **126**, the payment is accepted **127**. In case of payment by credit card **128**, the charge is confirmed to the bank **129** via the modem **71**. In case of payment by "smart

card", the card is debited **130** by the price of the goods.

The amount debited is stored **131** in the memory of the microprocessor and subsequently communicated **132** to an account clearing house as will be further explained below.

The modem **71** can be used to communicate via the Internet with a warehouse or
5 other type of control center, in order to provide information about the status of the vending machine such as the amount of goods already sold, proceeds received including the exact amount of currency which is now stored in the currency receptacle **46**. The microprocessor is programmed according to well-known techniques to initiate that kind of communication at preset intervals or specific times through a conventional phone network or via the Internet. The machine
10 activities and sale data that is compiled by, and stored by the microprocessor can be down-loaded on site by the service personnel on a recording medium, such as a smart-card, that is returned to the central location along with the expanded magazine. Alternately, the microprocessor can respond to polling calls initiated from the control center. From the information thus received at the control center, the most appropriate time when servicing personnel should be dispatched to
15 exchange the magazine of the machine can be determined. Moreover, the amount of money held in the currency receptacle, as well as the amount of goods remaining in the magazine are already known and can be verified upon receipt of the magazine. Any tampering or pilfering by the service personnel can thus be abated.

The preferred embodiment of the vending machine has a total height of 85
20 centimeters (33.5 inches), a total width of 72.5 centimeters (28.5 inches), and a total depth of 57 centimeters (22.5 inches), and an approximate weight of 34kilograms (75 pounds), including an empty magazine. Such a vending machine can be easily transported and installed on a table or

counter top where it occupies no more than 0.5 square meters (5.4 square feet).

The previously described vending machine **1** intended to dispense a variety of snack foods can be advantageously combined with a similar machine **75** intended to dispense beverage cans, more specifically illustrated in Figures 5-7. The beverage dispensing machine uses a cabinet **76** which is essentially similar to the one of the snack-vending machine, except that there is no currency acceptor, but accepts four side-by-side can magazines **77**. Each magazine is driven by only one motor assembly **60**. Accordingly, there is only one motor-driving module **61** mounted against the load compartment section of the liner **22**. In each of the four

magazines **77** up to twenty-four 12 ounce beverage cans are laid down one behind the other in a zig-zagging channel of a single cell **78**. The channel has five directionally alternating sections whose slanted, product-supporting floors **79** urge the can to roll toward a dispensing gate mechanism **80**. Beyond the gate an opening **81** in the bottom of the magazine allows the dispensed can to drop into the dispensing pocket **9**. The gate mechanism **80** comprises a horizontal shaft **82** joined to a coupling **83** in a lower section of the magazine back wall. This coupling is similar to the one used in connection with the spiral rack shaft of the first machine and is shaped and dimensioned to engage a corresponding coupling of one of the motor assemblies **60**. At the opposite end of the shaft, a first fan-shaped barrier is radially mounted so that when the shaft is rotated, this first barrier rises across the path of the lowermost can **85** in the channel. A second fan-shaped gate **86** is radially mounted on the shaft **82** in a direction opposite to that of the first barrier **84**, and at an axial distance corresponding approximately to the diameter of the can. Accordingly, when the first barrier is lowered by a 180° rotation of the shaft **82**, the second barrier rises between the first can **85** and the second can **87** positioned immediately behind it. As

the first can rolls out of the magazine through the opening **81**, the second can is held back by the second barrier **86** until the shaft completes a full rotation. At which time, the second barrier **86** is lowered below the slanted floor **79**. The second can **87** rolls down until it is stopped by the now raised first barrier **84**. Under the pull of gravity, all the remaining cans in the magazine roll
5 down one position. The mechanism is now ready for expelling the second can. The beverage can dispensing machine **75** includes a refrigerating assembly comprising a compressor **88** mounted under the angled plate **28**, a cooling coil **89** mounted against and above the ceiling portion **90** of the liner, and a condenser **91** mounted against the inner side of the back sheet **20**.

A power supply **73** is housed under the angled plate **28** next to the condenser. It
10 should be noted that the same cooling assembly can conveniently be provided in the snack-vending machine **1**.

It should also be noted that except for the passageway for the harness **74**, the liner **22** forms a seamless, hole-free wall surface. The harness passageway is automatically sealed when the insulating foam material is injected. Accordingly, the inside of the load compartment
15 and pocket can conveniently be cleaned and and sanitized with strong detergents or a germicidal solution. The absence of any metallic component or sensitive mechanism greatly expedites maintenance of the machines, and and enhances their reliability. If necessary, during cleaning and sanitiza-tion, the driving module **61** and the currency receptor **7** can conveniently be pulled out and disconnected from the harness **74**.

20 The use and profitability of the vending machine can be substantially increased by mounting a substitutable back-lit banner **134** as illustrated in Figure 5. The banner is held by lateral slots behind the window cut into the door of an auxiliary vending machine unit **75** that

dispenses only beverages. The beverage-dispensing machine does not require a transparent door to view the various available items. The type of available beverages can be indicated on a picture sign **132** located above the distribution pocket **9**.

The selection of the beverage and payment therefor is done on the keypad **6** and
5 by using the card reader **8** or currency acceptor of principal machine **1**. A simple umbilical cable **133** connects the two machines. A wide variety of enticing messages can be carried on the banner **134**, some messages may tout special packages combining a food item from the principal machine with a drink from the auxiliary machine at a reduced price. Entry of program commands can be made through the card reader **8**, via the modem **71**, or through wireless communication.

10 The currency acceptor **7** is not intended to accept and process currency in direct payment for the selected good to be dispensed by the machine. Its only purpose is to credit, that is reload a creditable and debitale smart card. In a separate transaction, the card can then be used to pay for the goods that have been selected by the user as previously explained.

The currency acceptor is preferably configured to accept bank notes in a plurality
15 of face amounts, typically, one, five, ten and twenty dollars or other national currency. The principal advantage of the currency acceptor system is that frequent users do not have to carry large amounts of coins, but only a wallet-sized card which can be used in connection with a variety of purchasing transactions as will be explained below.

As illustrated in Figures 10 and 11, as soon as the currency acceptor senses **135**
20 the insertion of currency in its entry slot, it causes the microprocessor program to check **136** whether a smart card has been introduced in the card reader **8**. If the card is not present, an appropriate instruction message is flashed **137** on the LCD display **72**. A ten second timer is

started **138**. If the timer expires **139** before the presence of a card in the card reader is detected, the currency is rejected **140**. If, or when, the smart card is detected in the card reader, the currency is processed **141**. First, it is tested for acceptability **142**. If the currency is not valid, it is rejected **140**. If it is validated, the smart card is credited **143** with a sum of money corresponding to the amount of currency accepted. A record of the accepted amount is stored **144** in the microprocessor memory. This information along with time and date of the transaction and the identification of the machine operator is subsequently transmitted **145** to an account clearing house through the modem **71**. This communication can take place concurrently with the acceptance of the currency. Alternately, it can be accomplished by later retrieval of the stored data and its communication over a transactional network such as the Internet at scheduled polling times.

As illustrated in Figure 11, the central account clearing house **146** communicates with a plurality of vending machines or other such automated transaction sites **147**, and maintains transaction ledgers for all accounts whose owners operate point-of-sale systems that share the same type of smart card. At the clearing house, each owners account is credited by the amount of money debited from a smart card in payment for a service or good purchased from an account owner. The account is debited by the amount of currency accepted by the account owner equipment.

The system allows the card holder access to a variety of services from a plurality of vendors that can be paid by means of a single universal smart card.

Each smart card can be conveniently reloaded at a number locations and through a variety of service terminals such as the instant vending machine.

A point-of-sale device comprising the above-described smart card debiting and crediting system and the currency acceptor may be used in connection with a variety of goods or service dispensing installations whether these goods or services are automatically vended by machines or personally provided by human beings.

5 The clearing-house may be constituted by a service-computer that monitors a number of vendor installations. As illustrated in Figure 12, the server, upon detecting **148** a communication from a vendor installation, first determines if a transaction is being reported **149**. If so, the server first looks to see if currency has been accepted **150** by the vendor's equipment. In which case, that particular vendor's account is debited **151** by the amount of currency accepted.
10 If currency acceptance is not being reported, the server looks for a sale amount being reported **151**. If so, the vendor's account is credited **153** with the reported sale amount. It should be noted that the smart cards need not be processed by the clearing-house, and act simply as convenient title instruments for the vending transactions.

 At the end of each month, or any other accounting period, the server reconciles all
15 vendors' accounts. Vendors who have collected more currency than the cost of goods or services they have dispensed are invoiced for the difference. Vendors who have sold more goods or services than the currency they have collected are notified of their accumulated credit amounts. Payment from the debtors to the creditors are preferably arranged through a financial institution or by a vendor association. Due to losses of smart-cards or their voluntary disposal by some
20 owners, the system is expected to generate surpluses that can be used to defer the cost of the clearing-house operation.

While the preferred embodiment of the invention has been described, modifications can be made and other embodiments may be devised without departing from the spirit of the invention and the scope of the appended claims

5

WHAT IS CLAIMED IS: